


0165

Diaphragm / piston pressure switches up to 250 V

ATEX 0102 CE  **II 2G Ex d II C T6 / T5 X (gas-protected zones 1 and 2)**

- Aluminium housing
- Snap action with silver contacts
- Operating voltage up to 250 V
- Overpressure safety up to 2,900 / 8,700 psi (200 / 600 bar)¹⁾

P _{max.} in psi (bar)	Adjustment range in psi (bar)	Tolerance in psi (bar) at room temperature	Thread	Order number
-----------------------------------	----------------------------------	---	--------	--------------

0165 Diaphragm pressure switches

2,900 psi ¹⁾ (200 bar) ¹⁾	14.5 - 87 psi (1 - 6 bar)	± 7.25 psi (± 0.5 bar)	1/4" BSPP female	0165 - 448 14 - 1 - 001
	72.5 - 725 psi (5 - 50 bar)	± 43.5 psi (± 3.0 bar)		0165 - 449 14 - 1 - 001

0165 Piston pressure switches

8,700 psi ¹⁾ (600 bar) ¹⁾	290 - 1,450 psi (20 - 100 bar)	± 43.5 - 72.5 psi (± 3.0 - 5.0 bar)	1/4" BSPP female	0165 - 450 14 - X - 001
	362.5 - 3,625 psi (25 - 250 bar)	± 72.5 - 101.5 psi (± 5.0 - 7.0 bar)		0165 - 452 14 - X - 001
	1,450 - 5,800 psi (100 - 400 bar)	± 72.5 - 130.5 psi (± 5.0 - 9.0 bar)		0165 - 451 14 - X - 001

Seal material – Application areas

NBR (BunaN)	Hydraulic/machine oil, heating oil, air, nitrogen, etc.	1
EPDM	Brake fluid, hydrogen, oxygen, acetylene, etc.	2
FKM (Viton®)	Hydraulic fluids (HFA, HFB, HFD), petrol/gasoline, etc.	3

Refer to page 82 for the temperature range and application thresholds of sealing materials

Your order number: 0165 - XXX 14 - X - 001

Piston pressure switches only have limited suitability for use with gases (refer to Page 14 for explanations).


M.8

ATEX




Contact assignment:

- 1 = white
- 2 = green
- 4 = brown



¹⁾ Static value. Dynamic value is 30-50 % lower. Values pertain to the hydraulic/pneumatic part of the pressure switch.



Explosion-protected pressure switches

Technical data

Type:	0165	0340 / 0341	
ATEX protection zone:	1 and 2	22	
Combustible Material:	Gases and vapours	Dusts	
Rated working voltage:	10 ... 250 VAC	10 ... 250 VDC	10 ... 250 VAC
Rated working current:	10 mA ... 1 A	10 mA ... 250 mA	10 mA ... 2 A
Temperature resistance:	NBR (BunaN)	-4 °F... +176 °F (-20 °C... +80 °C)	
	EPDM	-4 °F... +176 °F (-20 °C... +80 °C)	
	FKM (Viton®) (in diaphragm pressure switch)	+23 °F... +176 °F (-5 °C... +80 °C)	
	FKM (Viton®) (in piston pressure switch)	+5 °F... +176 °F (-15 °C... +80 °C)	
Switching frequency:	200 / min.		
Mechanical life expectancy:	1,000,000 cycles		
Pressure rise rate:	≤ 14.5 psi/ms (≤ 1 bar/ms)		
Differential:	10 ... 30 % (depending on type, non-adjustable)		
Vibration resistance:	10 g; 5 ... 200 Hz sine wave; DIN EN 60068-2-6		
Shock resistance:	294 m/s ² ; 14 ms half sine wave; DIN EN 60068-2-27		
Cable length:	Standard length approx. 6.5 ft (2 m) with wire end sleeve, also available in lengths of approx. 16 ft (5 m).		
Cable cross-section:	3 x 0.75 mm ²	3 x 0.5 mm ²	
Housing material:	Aluminium	Zinc-plated steel (CrVI-free) anodised aluminium	
Protection class:	IP65		
Weight:	approx. 13.5 oz (380 g)		approx. 8.2 oz (230 g)

Explosion-protected pressure switches

Technical data

M.8

ATEX



Technical explanations

Explosion-protected pressure switches are classified according to the respective combustible material type. This division is:

Gases and vapours 0165	Dusts 0340 / 0341	Methane dust not suitable
---	------------------------------------	--

Our pressure switches are generally designed for use with gases, vapours or dust.

Our explosion-protected pressure switches are not approved for use with methane dust (mining applications).

The table provides an overview of the zone divisions, equipment groups and equipment categories.

Conditions in potentially explosive atmosphere

Com- bustible materials	Temporary behaviour of combustible materials in potentially explosive area	Categori- sation of potentially explosive areas	Marking required on equipment to be used	
			Equipment group	Equipment category
Gases Vapours	are present continually, frequently or for long periods	Zone 0	II	1G
	occur occasionally	Zone 1	II	2G or 1G
	are unlikely to occur, and if so, are then only seldom or for short periods	Zone 2	II	3G or 2G or 1G
Dusts	are present continually, frequently or for long periods	Zone 20	II	1D
	occur occasionally	Zone 21	II	2D or 1D
	occur if accumulated dust is whirled up, and then only seldom or for short periods	Zone 22	II	3D or 2D or 1D
Methane dust	-	Mining industry	I	M1
	-	Mining industry	I	M1 or M2



Explosion-protected pressure switches

To ATEX standard



- ATEX-certification for use in potentially explosive areas
- Switching point can be easily adjusted by the user whilst system is in operation
- Compact design
- Excellent price/performance ratio