

# PMD-MXT Series Digital Temperature Scanner Indicator

## Features

- Accepts 8, 16, 24 or 32 input channels
- Visible high & low temperature alarm LEDs
- Displays in °F or °C (User selectable)
- RS-485 Communications for remote operation
- Independent dual HI/LO temperature alarms

## Applications

- Factory Automation
- Process Control
- R&D Testing



## Overview

The PMD-MXT series Thermocouple/RTD scanner is perfect for any multi-point temperature measurement application. The bright red LED display is easy to read, even at a distance.

Splash-resistant front panel keypad is easy to clean & wipe down.

The indicator has 2 user-selectable HI/LO, HI/HI, or LO/LO alarm set points, configured through the front panel push buttons. During an alarm condition a front panel LED annunciator is enabled & an internal 2 Amp relay contact output is engaged.

The indicator display will cycle through all input channels at a user determined rate of 0.5~10 seconds.

24 VDC powered. A must have for multi-point temperature monitoring in the Lab, control room, or Dynamometer.

## Specifications

<b>Input type:</b>	RTD: PT100, CU100, CU50
	Thermocouple: J, K, T, B, E, N, R, S
<b>Accuracy:</b>	RTD: +/- 1.0% of full scale
	Thermocouple: +/- 0.5% of full scale
<b>Resolution:</b>	RTD (0.1° Res): -167.9 to +999.9°F (-189.9 to +596.9°C)
	TC (0.1° Res): -167.9 to +999.9°F (-199.9 to +999.9°C)
	TC (1° Res): -412 to 3271°F (-257 to 1800°C)
<b>Display:</b>	4-digit LED, 0.56 inch (14 mm high)
<b>Sample Rate:</b>	0.1 second per channel
<b>Power:</b>	20 to 28 VDC @ 400 mA (nominal)
<b>Dimensions:</b>	6.3 inch x 3 inch x 7 inch (160 mm x 80 mm x 182 mm) (Cutout: 6 inch x 3 inch (152 mm x 76 mm))
<b>Weight:</b>	2 pounds (900 grams)
<b>Relay contact:</b>	250 VAC @ 2 amps (resistance load)
<b>Environment:</b>	0 to 50°C, 90% Max. RH (non-condensing)

